

Printing date 03.08.2006

Reviewed on 24.07.2006

1 Identification of the substance/preparation and of the company/undertaking

- · Product details
- · Trade name: Acrylic acid Glacial
- Manufacturer/Supplier: Petrochem Middle East FZE PO Box 17028, Jebel Ali Free Zone Dubai, UAE Ph +971 4 8839222; Fax +971 4 8834133
- · Further information obtainable from: Product safety department.

2 Composition/information on ingredients

- · Chemical characterization:
- CAS No. Description 79-10-7 acrylic acid
- · *Identification number*(s)
- EINECS Number: 201-177-9
- EU Number: 607-061-00-8

## **3 Hazards identification**

· Hazard description:



C Corrosive N Dangerous for the environment

Information concerning particular hazards for human and environment:

R 10 Flammable.

R 20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

*R 35 Causes severe burns.* 

*R* 50 *Very toxic to aquatic organisms.* 

#### 4 First aid measures

• General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:
- Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

UAE

(Contd. on page 2)



Printing date 03.08.2006

Reviewed on 24.07.2006

Trade name: Acrylic acid Glacial

(Contd. of page 1)

### **5** Fire-fighting measures

- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Protective equipment: Mouth respiratory protective device.

### 6 Accidental release measures

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- Measures for environmental protection: Inform respective authorities in case of seepage into water course or sewage system. Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water.
  Measures for cleaning/collecting: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

## 7 Handling and storage

· Handling:

- · Information for safe handling: Ensure good ventilation/exhaustion at the workplace.
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke.*

Protect against electrostatic charges.

- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

#### 8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with	limit values that	t require	monitoring	at the	workplace:

acrylic acid	
REL (USA)	6 mg/m <sup>3</sup> , 2 ppm Skin 5.9 mg/m <sup>3</sup> , 2 ppm Skin
	Skin
TLV(USA)	5.9 mg/m³, 2 ppm
	Skin

• Additional information: The lists valid during the making were used as basis.

· Personal protective equipment:

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.



Printing date 03.08.2006

Reviewed on 24.07.2006

Trade name: Acrylic acid Glacial

(Contd. of page 2)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation  $\cdot$  *Material of gloves* 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

• General Information	
Form:	Fluid
Colour:	Colourless
Odour:	Pungent
• Change in condition	
Melting point/Melting range	e: 13°C
<b>Boiling point/Boiling range</b>	: 141°C
Flash point:	54°C
Ignition temperature:	374°C
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixture, are possible.
Explosion limits:	
<i>Lower:</i>	5.3 Vol %
Upper:	26 Vol %
• Vapour pressure at 20•C:	4.3 hPa
Density at 20°C:	1.0511 g/cm <sup>3</sup>
· Solubility in / Miscibility with	
water:	Fully miscible.

## **10 Stability and reactivity**

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Dangerous reactions No dangerous reactions known.

(Contd. on page 4)

Printing date 03.08.2006

Chemtrade Overseas

Reviewed on 24.07.2006

Trade name: Acrylic acid Glacial

PRIVATE LIMI

• Dangerous decomposition products: No dangerous decomposition products known.

(Contd. of page 3)

### **11 Toxicological information**

#### · Acute toxicity:

· LD/LC50 values relevant for classification:

Oral LD50 250 mg/kg (rat) Dermal LD50 280 mg/kg (rabbit)

#### · Primary irritant effect:

- on the skin: Strong caustic effect on skin and mucous membranes.
- · on the eye: Strong caustic effect.
- Sensitization: No sensitizing effects known.
- $\cdot$  Additional toxicological information:

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

## **12 Ecological information**

- · Ecotoxical effects:
- · Remark: Very toxic for fish
- · General notes:

Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralized. Also poisonous for fish and plankton in water bodies. Very toxic for aquatic organisms

## **13 Disposal considerations**

· Product:

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

## **14 Transport information**

· Land transport ADR/RID (cross-border)



• ADR/RID class: 8 Corrosive substances.

- Danger code (Kemler): 839
- · UN-Number: 2218 · Packaging group: II
- Hazard label: 8+3

(Contd. on page 5)

UAE


Printing date 03.08.2006

Chemtrade Overseas

Reviewed on 24.07.2006

Trade name: Acrylic acid Glacial

PRIVATE LIMITED



#### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS: Product safety department.

· Contact: Terminal Manager