

Printing date 03.08.2006 Reviewed on 24.07.2006

1 Identification of the substance/preparation and of the company/undertaking

· Product details

· Trade name: methyl methacrylate

· Manufacturer/Supplier:

Petrochem Middle East FZE PO Box 17028, Jebel Ali Free Zone

Jebel All Free Zone

Dubai, UAE

Ph +971 4 8839222; Fax +971 4 8834133

· Further information obtainable from: Product safety department.

2 Composition/information on ingredients

- · Chemical characterization:
- · CAS No. Description

80-62-6 methyl methacrylate

- · Identification number(s)
- · EINECS Number: 201-297-1
- · EU Number: 607-035-00-6

3 Hazards identification

· Hazard description:





Xi Irritant

F Highly flammable

- · Information concerning particular hazards for human and environment:
- R 11 Highly flammable.
- R 37/38 Irritating to respiratory system and skin.
- R 43 May cause sensitisation by skin contact.

4 First aid measures

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

5 Fire-fighting measures

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Protective equipment: No special measures required.

- UA



Printing date 03.08.2006 Reviewed on 24.07.2006

Trade name: methyl methacrylate

(Contd. of page 1)

6 Accidental release measures

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- · Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.
- · Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

7 Handling and storage

- · Handling:
- · Information for safe handling: No special requirement
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:		
80-62-6 methyl methacrylate		
PEL (USA)	410 mg/m³, 100 ppm	
REL (USA)	410 mg/m³, 100 ppm	
TLV(USA)	Short-term value: 410 mg/m³, 100 ppm	
	Long-term value: 205 mg/m³, 50 ppm	
	SEN	
WEL (Great Britain)	Short-term value: 416 mg/m³, 100 ppm	
	Long-term value: 208 mg/m³, 50 ppm	

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 3)



Printing date 03.08.2006 Reviewed on 24.07.2006

Trade name: methyl methacrylate

(Contd. of page 2)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· General Information	
Form:	Fluid
Colour:	Colourless
Odour:	Acrid
· Change in condition	
Melting point/Melting range:	-48°C
Boiling point/Boiling range:	101°C
· Flash point:	10°C
· Ignition temperature:	430°C
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	2.1 Vol %
Upper:	12.5 Vol %
· Vapour pressure at 20°C:	47 hPa
· Density at 20°C:	0.94 g/cm³
· Solubility in / Miscibility with water at 20°C:	1.6 g/l

10 Stability and reactivity

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Acute toxicity:
- · LD/LC50 values relevant for classification:

Oral LD50 7872 mg/kg (rat)

(Contd. on page 4)

(Contd. of page 3)



Material Safety Data Sheet According to 91/155 EEC

Printing date 03.08.2006 Reviewed on 24.07.2006

Trade name: methyl methacrylate

· Primary irritant effect:

- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.

12 Ecological information

General notes:

Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- · Product:
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· Land transport ADR/RID (cross-border)



· ADR/RID class: 3 Flammable liquids.

Danger code (Kemler): 339
UN-Number: 1247
Packaging group: II
Hazard label: 3

Description of goods: 1247 METHYL METHACRYLATE MONOMER, STABILIZED

· Maritime transport IMDG:



IMDG Class: 3
UN Number: 1247
Label 3
Packaging group: II
EMS Number: F-E,S-D

· Proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED

(Contd. on page 5)



Printing date 03.08.2006 Reviewed on 24.07.2006

Trade name: methyl methacrylate

(Contd. of page 4)

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 3 · UN/ID Number: 1247 · Label 3 · Packaging group: II

· Proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED

15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:

Xi Irritant

F Highly flammable

- · Risk phrases:
- 11 Highly flammable.
- 37/38 Irritating to respiratory system and skin.
- 43 May cause sensitisation by skin contact.
- · Safety phrases:
- 2 Keep out of the reach of children.
- 24 Avoid contact with skin.
- 37 Wear suitable gloves.
- 46 If swallowed, seek medical advice immediately and show this container or label.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Product safety department.
- · Contact: Terminal Manager

UAE